


QR code for Installations Instructions



The unit must be installed by a qualified electrician in accordance with all national and local electrical and construction codes and regulations.




STEP 1
 CEILING OPENING




Prepare mounting hole with diameter of 90mm.

STEP 2
 CONNECTION OF CONTROL UNIT



Connect all power and data wires to Control unit before mouning it into the ceiling.

PRIMARY POWER CONNECTION



Install terminal block to power cable (from Ambiane Power Rack or Ambiane Power HP) and connect it to Primary power socket of the control unit.


DATA (DMX OR DALI) AND SECONDARY POWER CABLES CONNECTION

SECONDARY POWER CONNECTION

TERMINAL BLOCK	0V	VCC
Colour of Wire	BLUE	RED


DMX CONNECTION

TERMINAL BLOCK	0V	D-	D+
Function	Data Ground	Data -	Data +




Install terminal blocks on SECONDARY POWER and DATA cables and connect them to the control unit. Set the DIP switches to positions according to your operation mode. The fixture can be controlled by DMX or DALI (switch 11 in OFF position).

STEP 3
MOUNTING WITH SPRING CLIPS




1




Lift up spring clips on both sides.

2



Insert luminaire into ceiling opening.

3



Release spring clips to hold luminaire in place.