

# E-BOX™ DAISY

Giving designers unlimited creativity options, the E-Box Daisy is a single output device specifically designed for long-run installations, allowing the connection of up to 144 Eminere 1 luminaires in combination with Ethernet control.

**E-Box Series** | Offering architectural lighting designers a new way of implementing creativity and innovative technology into the visual experience, our Eminere series is powered by a comprehensive range of E-Box control systems. Based on the unique installation requirements of each project, the E-Box Lite, E-Box Daisy, and E-Box Star power and data connection devices provide a high level of design flexibility.



## KEY FEATURES

### Output

One fixture power and data output for connecting up to 144 Eminere 1 luminaires

### Control

E-box can be easily configured by its LCD display. In stand-alone mode, you can make three programs on your own containing up to 40 steps. Control is possible through a wide variety of protocols (DMX512/RDM, Art-Net, MA-Net, MA-Net2, sACN, Kling-Net), and thanks to lumen radio CRMX technology, there is also a wireless DMX option.

### Physical

The durable housing provides both IK10 and IP67 protection ratings.


## STANDARD & SPECIFICATION



## FINISH OPTIONS



## DIMENSIONS



**E-BOX DAISY SPECIFICATION**

<b>ELECTRICAL</b>	Input Voltage	120 - 277 V AC 50 / 60 Hz	
	Typical Power Consumption	5W (self consumption)	
	Max. Output Current	16A	
<b>CONTROL</b>	Wireless DMX (Option)	Lumen Radio CRMX Technology	
	Interface Protocol	USITT DMX512, RDM, ArtNet, MA Net, MA Net2, sACN, Kling-Net	
	Operating Modes	DMX, Stand-alone	
	Display	Two Row LCD and Control Buttons	
<b>PHYSICAL</b>	Width x Height x Depth	260 x 160 x 91 mm (10.24 x 6.3 x 3.58 in.)	
	Weight	2.78 kg / 6.13 lbs	
	Number of LED Output zones	1	
	Max. Load Per Output		144 pcs of Eminere 1 with 40 m total cable length @ 230 V
			78 pcs of Eminere 2 with 30 m total cable length @ 230 V
			53 pcs of Eminere 3 with 30 m total cable length @ 230 V
			40 pcs of Eminere 4 with 30 m total cable length @ 230 V
	DMX Modes	Fixture Mode, Pixel Mode, Output Mode	
	Editable Programs	3 (up to 40 steps each)	
	Eminere Output Connection	Leader Cable - Combo Power and Data	
	Finish Options		Standard Colour - Graphite Black (RAL 9011)   Silver (RAL 9006)
			Cost Option - Custom RAL   Harsh Environment (RAL 9016, RAL 9011)
	Mounting Method	4 Mounting Holes	
Protection Factor	IP67, Suitable For Wet Location		
IK Rating	IK10		
Cooling System	Convection		
Operating Temperature Range	-20 °C / +40 °C (-4 °F / +104 °F)		
<b>CERTIFICATION</b>	Listings	ETL / cETL, CE, RoHS	

**CONNECTION**

