

E-BOX™ LITE

Featuring a single combined power and data output which can connect up to 144 Eminere 1 luminaires, with control via wired DMX or optional wireless DMX for hard to access areas, the E-Box Lite is the ideal combination of technology standards and cost effectiveness.

E-Box Series | Offering architectural lighting designers a new way of implementing creativity and innovative technology into the visual experience, our Eminere series is powered by a comprehensive range of E-Box control systems. Based on the unique installation requirements of each project, the E-Box Lite, E-Box Daisy, and E-Box Star power and data connection devices provide a high level of design flexibility.



KEY FEATURES

Output

One fixture power and data output provides an economical solution for a more simple installation where 159 Eminere luminaires can be connected to the input when the cable length is approximately 30 m (power voltage 230 V).


Control

E-Box Lite can be easily configured by its LCD display. In stand-alone mode, you can make three programs on your own containing up to 40 steps. Control is possible through two protocols (DMX512/RDM) and thanks to lumen radio CRMX technology, there is also a wireless DMX option.

Physical

E-Box Lite is compact solution providing great durability through its IP67 and IK10 certifications.

STANDARD & SPECIFICATION




FINISH OPTIONS

* CLOSEST RAL TONE
* HE = Harsh Environment



DIMENSIONS



E-BOX LITE SPECIFICATION

ELECTRICAL	Input Voltage	120 - 277 V AC 50 / 60 Hz	
	Typical Power Consumption	5W (self consumption)	
	Max. Output Current	16A	
CONTROL	Wireless DMX (Option)	Lumen Radio CRMX Technology	
	Interface Protocol	USITT DMX512, RDM	
	Operating Modes	DMX, Stand-alone	
	Display	Two Row LCD and Control Buttons	
PHYSICAL	Width x Height x Depth	220 x 81 x 120 mm (8.66 x 3.18 x 4.72 in.)	
	Weight	1.67 kg / 3.85 lbs	
	Number of LED Output zones	1	
	Max. Load Per Output		144 pcs of Eminere 1 with 40 m total cable length @ 230 V
			78 pcs of Eminere 2 with 30 m total cable length @ 230 V
			53 pcs of Eminere 3 with 30 m total cable length @ 230 V
			40 pcs of Eminere 4 with 30 m total cable length @ 230 V
	DMX Modes	Fixture Mode, Pixel Mode, Output Mode	
	Editable Programs	3 (up to 40 steps each)	
	Eminere Output Connection	Leader Cable - Combo Power And Data	
	Finish Options	Standard Colour	Graphite Black RAL 9011 Grey Aluminium RAL 9007 Pure White RAL 9010 Sandstone RAL 1014
		Harsh Environment	Graphite Black RAL 9011 Grey Aluminium RAL 9007 Pure White RAL 9010 Sandstone RAL 1014
		Cost Option	Custom RAL
	Mounting Method	4 Mounting Holes	
Protection Factor	IP67, Suitable For Wet Location		
IK Rating	IK10		
Cooling System	Convection		
Operating Temperature Range	-20 °C / +40 °C (-4 °F / +104 °F)		
CERTIFICATION	Listings	ETL / cETL, CE, RoHS, UKCA	

CONNECTION

