

CALUMMA™ CATENARY M SC

Featuring an optical design using 37 high efficacy single-chip LEDs and available with optional LED colour variants and various beam angles, the medium-sized Calumma Catenary M SC luminaire creates powerful and beautiful light output for a spot or flood lighting solution. Its durable housing is built to withstand any exterior conditions, and its special finish for harsh and marine environments provides an exceptional outdoor LED luminaire in an elegant design.



KEY FEATURES

Lumen output & Light source

Luminaire with 37 high-power, singlechip LEDs provides up to 3478 lumen output. Multiple LED colour variants. No light spills. Well homogenised light output with great efficacy up to 57 lm/w.

Design & Durability

Compact, durable and stylish housing made of high-pressure die cast aluminium. IP67 and IK10 certification; suitable for marine applications (Harsh Environment Finish required) and traffic applications. Supported with a 5 year warranty.

Flexibility

Exceptional outdoor or indoor LED luminaire with a custom colour finishes, multiple light output variants and beam angles.

Connectivity

Utilising the innovative E-Box series of power and data interfaces, Calumma Catenary M SC can communicate via numerous control protocols.

COLOURS

* UPON REQUEST




CONTROL & PROTOCOLS




OPTIC OPTIONS

SYMMETRICAL




BI-SYMMETRICAL



COLOUR TEMPERATURE

* UPON REQUEST



STANDARD & SPECIFICATION



FINISH OPTIONS

* CLOSEST RAL TONE
* HE = Harsh Environment




SPECIFICATION

ELECTRICAL	Input Voltage	120 - 277 V AC 50/60 Hz (US)		
	Typical Power Consumption	60 W +/-10 %		
OPTICAL	Light Source	37x High Power Single Chip LEDs		
	Colour Variants	RGBW (W - 6500 K) RGBA PW (W - 3000 K)		
		Other Variants On Request (TW (2700 - 6500 K), 2200 K, 2500 K, 2700 K, 3500 K, 4000 K, 5000 K, 6500 K)		
	Beam Angle	10° 15° 25° 30° 45° 65° 100°		
		10°x30° 30°x10° 10°x60° 60°x10° 15°x45° 45°x 15° 15°x90° 90°x15° 30°x60° 60°x30° 30°x90° 90°x30°		
	Lumen Output Delivered	3478 lm (@10° RGBW)		
Projected Lumen Maintenance	L90B10 >90.000 hrs, Ta = 25°C / 77°F			
CONTROL	Interface Protocol	Via E-box range, DMX/RDM, DALI 2		
	E-box control protocol	USITT DMX512+RDM, ArtNet, MA Net, MA Net2, sACN, Kling-Net		
	DALI 2 Device Type	DT 8		
	Control System	Third Party DMX Controllers or third party DALI 2 controllers, Ethernet		
	Operating Modes	DMX, Stand-alone		
	Settings / Addressing	E-Box, RDM communicator		
	Power Supply	Integrated		
PHYSICAL	Width x Height x Depth Weight	264 x 238 x 236 mm (10.4 x 9.37 x 9.3 in.) 7.4 kg (16.31 lbs)		
	Housing	High Pressure Die-Cast Aluminium Body Tempered Glass		
	Finish Options	Standard Colour	Graphite Black RAL 9011 Grey Aluminium RAL 9007 Pure White RAL 9010 Sandstone RAL 1014	
		Standard Colour Harsh Environment	Graphite Black RAL 9011 Grey Aluminium RAL 9007 Pure White RAL 9010 Sandstone RAL 1014	
		Cost Option	Custom RAL	
	Cables / Connections	Integrated Junction Box		
	Mounting Method	Catenary Mounting / Mounting Brackets		
	Adjustability	+180° / -180°		
	Protection Factor	IP67 / Suitable For Wet Locations		
	IK Rating	IK10		
	Cooling System	Convection		
Operating Ambient Temperature	-20 °C / +50 °C (-4 °F / +122 °F)			
CERTIFICATION	Listings	ETL / cETL, CE, RoHS, UKCA		
ACCESSORIES	Not Included Items			
	Junction Box CE or US			
	Optical Demo Set for Calumma M (for demo purposes)			
	Outdoor Foil Holder for Calumma M „OFH“ version only (for permanent installation)			
	Optical Foil Set for Outdoor Foil Holder Calumma M			
	Cable hybrid 3xAWG 16 + 1x (2xAWG 24) (CE, black) - for DMX or E-Box versions			
	Cable HYB-5731ZH LSZH (CE, white) - for DMX or E-Box versions			
	Cable SJTW 6x AWG 14 (US, black) - for E-Box versions			
	Cable SJTW 6x AWG 14 (US, white) - for E-Box versions			
	Re-enterable Electrical Insulating Resin			

CONTROL AND CONNECTION OPTIONS - CE


DALI

- 1) Junction Box
- 2) Hybrid Cable (1305 3693), bare-end
- 3) Hybrid Cable (1305 3693) or Scope of Others




DMX

- 1) Junction Box
- 2) Flamar 3x AWG 16 + 1 x (2x AWG 24) black, bare-end (1305 1508), or Hybrid Cable HYB-5731ZH LSZH white (1305 3694)
- 3) Flamar 3x AWG 16 + 1 x (2x AWG 24) black (13051508), or Hybrid Cable HYB-5731ZH LSZH white (1305 3694), or Scope of Others



DMX or ETHERNET via E-BOX


- 1) Flamar 3x AWG 16 + 1 x (2x AWG 24), (13051508), black, or Hybrid Cable HYB-5731ZH LSZH (13053694) white, or Scope of Others
- 2) Flamar 3x AWG 16 + 1x (2x AWG 24) (13051508), bare-end, black, or Hybrid Cable HYB-5731ZH LSZH (13053694), white



CONTROL AND CONNECTION OPTIONS - US


DALI

- 1) Junction Box
- 2) SJTW 5x 14AWG (13053336), bare-end, black, or Cable SJTW 5x 14AWG (13053697), white
- 3) SJTW 5x 14AWG (13053336), black, or Cable SJTW 5x 14AWG (13053697), white, or Scope of Others



DMX or ETHERNET via E-BOX

- 1) SJTW 6x 14AWG (13053480), black, or Cable SJTW 6x 14AWG (13053695), white, or Scope of Others
- 2) SJTW 6x 14AWG (13053480), bare-end, black, or Cable SJTW 6x 14AWG (13053695), white




CONNECTIVITY

Following table shows maximum connected Calummas M SC in a row with respect of cable length.

STANDARD MODE	Cable length (m)	Voltage (V)			
		120	190	230	277
CALUMMA M SC	10	30	48	58	70
	20	30	48	58	70
	30	21	48	58	70
	50	13	32	47	68
	70	9	23	34	49
	100	6	16	24	34
	200	3	8	12	17
	500	1	3	5	7

PASS-THROUGH MODE	Cable length (m)	Voltage (V)			
		120	190	230	277
CALUMMA M SC	10	30	32	32	32
	20	30	32	32	32
	30	21	32	32	32
	50	13	32	32	32
	70	9	23	32	32
	100	6	16	24	32


DIMENSIONS



ACCESSORIES

Outdoor Foil Holder for Calumma M


Outdoor Foil Holder for Calumma M „OFH“ version only (for permanent installation). **Example of ordering code:** Calumma M SC CE RGBCW 10° RAL9007 OFH



BI-SYMMETRICAL BEAM ANGLES

Bi-symmetrical:
10°x30°,
10°x60°,
15°x45°,
15°x90°,
30°x60°,
30°x90°


10°, 15°, 30°



30°, 45°, 60°, 90°

Bi-symmetrical:
30°x10°,
60°x10°,
45°x15°,
90°x15°,
60°x30°,
90°x30°



30°, 45°, 60°, 90°





10°, 15°, 30°

PHOTOMETRIC DATA



Calumma M SC RGBW 6500K 10dg





Calumma M SC RGBW 6500K 15dg





Calumma M SC RGBW 6500K 25dg





Calumma M SC RGBW 6500K 30dg



Calumma M SC RGBW 6500K 45dg



Calumma M SC RGBW 6500K 65dg



Calumma M SC RGBW 6500K 100dg

