

LYRAE™ S SC

Difficult inground installations are made easier with the Lyrae S SC. High light output comes from powerful LEDs and it can be used with a variety of optics, from narrow to wide, in addition to a bi-symmetrical option. The light source can be remotely tilted 25° from the horizontal position, always ensuring accurate illumination of the selected surface. Additionally, Lyrae S SC can be equipped with anti-skid glass featuring the highest standards of certification for anti-slip usage having no impact on the fixture's outstanding colour mixing.




KEY FEATURES

Lumen output & Light source
Providing perfectly mixed colour with luminous flux up to 1422 lm (@ PW 3000K), the 27 W Lyrae S SC luminaire utilises LEDs with 10° optics. Its excellent lumen maintenance of 90,000 hrs (L90B10) provides a dependable and long-term lighting installation.

Physical
Protected underground by high-pressure, die-cast aluminum, the above-ground stainless steel and glass cover provides an elegant and durable lighting solution in all kind of weather. The glass cover can be clear or with anti-skid treatment for inground applications, and its durability is guaranteed by IP67 and IK10 certification.


COLOURS

* UPON REQUEST



COLOUR TEMPERATURE

* UPON REQUEST




CONTROL & PROTOCOLS




OPTIC OPTIONS

SYMMETRICAL



BI-SYMMETRICAL




STANDARD & SPECIFICATION



TRIM FINISH OPTIONS



TRIM OPTIONS




SPECIFICATION


ELECTRICAL	Input Voltage	120–277 V AC 50/60 Hz		
	Typical Power Consumption	30 W +/-10 %		
OPTICAL	Light Source	High Power Single Chip LEDs		
	Colour Variants	PW (3000 K)		
		Variants On Request (TW (2200–4000 K 2700–6500 K) 2200 K 2700 K 4000 K 6500 K)		
		Beam Angle	Clear Glass	Symmetrical: 10° 15° 25° 30° 45° 65° Bi-symmetrical: 10°x30° 30°x10° 10°x60° 60°x10° 15°x45° 45°x15° 30°x60° 60°x30°
			Anti-Skid Glass	Symmetrical: 18° 22° 35° 50° (preliminary) Bi-symmetrical: 20°x35° 35°x20° 20°x65° 65°x20° 20°x50° 20°x50° 35°x65° 65°x35° (preliminary)
	Lumen Output Delivered	1422 lm (@10° PW 3000 K)		
	Projected Lumen Maintenance	L90B10 >90.000 hrs, Ta = 25°C / 77°F		
	CONTROL	Interface Protocol	DMX/RDM DTP DALI 2 NFC	
Operating Modes		DMX, Stand-alone		
Settings / Addressing		RDM NFC (Stand-alone)		
Power Supply		Integrated		
PHYSICAL	Flange Diameter x Diameter x Height	Bevel Egde Trim: ø 210 x ø 353 x 280 mm (ø 8.3 x ø 14 x 11.1 in.)		
	Weight	3.75 kg 8.16 lbs		
	Housing	High Pressure Die-Cast Aluminium Body Stainless Flange Tempered Glass (Clear or Anti-Skid)		
	Trim Options	Bevel Edge Trim Flush Trim		
	Trim Shape	Round Square		
	Trim Finish Options	Stainless steel		
	Cables / Connections	Integrated Junction Box		
	Mounting Method	External Mounting Sleeve		
	Adjustability	Motorised Tilt 0°–25° (One Direction Tilt) - Setting-up via NFC (password protected), or DMX		
	Protection Factor	IP67 / Suitable For Wet Locations (8h @ 1m)		
	IK Rating	IK10		
	Static Load Resistance	35 kN (TBC)		
	Cooling System	Convection		
	Operating Ambient Temperature	-20°C / +40°C (-4°F / +104°F)		
CERTIFICATION	Listings	ETL / cETL, CE, RoHS, UKCA		
ACCESSORIES	Not Included Items			
		Lyrae S Mounting Sleeve		
		Lyrae S Trim Holder		
		Junction Box (CE or US)		
		Trim for Lyrae S (Stainless Steel, Round, Bevel Edge)		
		Trim for Lyrae S (Stainless Steel, Round, Flush)		
		Trim for Lyrae S (Stainless Steel, Square, Bevel Edge)		
		Re-enterable Electrical Insulating Resin		
		Rock Guard		
DEMO SET	Lyrae S Demo Set	Includes: Lyrae fixture, Mounting Sleeve, Trim, Set of Optical Foils (Not suitable for permanent instalations. IP2X.)		

DIMENSIONS


Lyrae S Trim Holder (Direct installation into pre-formed solid base; no sleeve required.)




with Round beveled Trim



with Square beveled Trim



with Round flush Trim




CONTROL AND CONNECTION OPTIONS - CE

DALI

Example of ordering code: Lyrae S SC RGBCW 15° DALI

- 1) Junction Box
- 2) Hybrid Cable (1305 3693)
or Scope of Others


Note: All Anolis cables must be in placed in protective conduit – not suitable for direct burial.



DMX

- 1) Junction Box
- 2) Cable (1305 1508)


Note: All Anolis cables must be in placed in protective conduit – not suitable for direct burial.



DMX or ETHERNET via E-BOX

- 1) Cable CE WCA (1305 3138)

Note: All Anolis cables must be in placed in protective conduit – not suitable for direct burial.




CONTROL AND CONNECTION OPTIONS - US

DALI

Example of ordering code: Lyrae S SC RGBCW 15° DALI

- 1) Junction Box
- 2) SJTW 5x 14AWG (1305 3336), black or Scope of Others


Note: All Anolis cables must be in placed in protective conduit – not suitable for direct burial.



DMX or ETHERNET via E-BOX

- 1) Cable US WCA (1305 3139)


Note: All Anolis cables must be in placed in protective conduit – not suitable for direct burial.



BI-SYMMETRICAL BEAM ANGLES

Bi-symmetrical:

- 10°x30°,
- 10°x60°,
- 15°x45°,
- 30°x60°



Bi-symmetrical:

- 30°x10°,
- 60°x10°,
- 45°x15°,
- 60°x30°

