

# CALUMMA™ ARTS XS SC

Calumma Arts XS SC is a compact architectural luminaire with a strong artistic character, designed to transform light into a creative expression. Featuring high-power single-chip LED technology, it is available with precise 10° optics or without optics, and offers a choice of 4 interchangeable lenses and 9 textured glass options to create layered projections and an exceptionally wide variability of final lighting effects. The optical system can be customized directly on site, allowing designers to fine-tune the output to perfectly suit the installation. With its durable IP67-rated housing, wide control compatibility and elegant design, Calumma Arts XS SC delivers versatile, expressive lighting for distinctive architectural applications.



## KEY FEATURES

### Lumen output & Light source

Luminaire with four high-power, single-chip LEDs provides up to 457 lumen output (@10°, PW 3000 K). No light spills.


### Design & Durability

Lightweight, compact, durable and stylish housing made of high-pressure die cast aluminium. IP67 and IK10 certification; suitable for marine applications (Harsh Environment Finish required) and traffic applications. Supported with a 5 year warranty.

### Flexibility


An exceptionally compact luminaire available with a wide range of accessories and custom colour finishes, Calumma Arts XS SC offers lighting designers a highly flexible solution based on interchangeable lenses and textured glass elements that can be freely combined to create unique, original lighting effects for the most demanding applications.

## TEXTURED GLASS



## COLOURS


\* UPON REQUEST




## CONTROL & PROTOCOLS



## STANDARD & SPECIFICATION




## LENSES




## COLOUR TEMPERATURE

\* UPON REQUEST




## OPTIC OPTIONS



## FINISH OPTIONS

\* CLOSEST RAL TONE  
\* HE = Harsh Environment



**SPECIFICATION**


|   |  |   |   |  |
|---|--|---|---|--|
| <b>ELECTRICAL</b>                         | Input Voltage  | 48 V  |   |  |
|   | Typical Power Consumption  | 10 W +/-10 %  |   |  |
| <b>OPTICAL</b>                            | Light Source   | High Power Single Chip LEDs   |   |  |
|   | Colour Variants  | PW (W - 3000 K)<br><b>On Request:</b> TW (2700–6500 K), 2200 K, 2500 K, 2700 K, 3500 K, 4000 K, 5000 K, 6500 K        |   |  |
|   | Beam Angle   | 10°   No Optics   |   |  |
|   | Lumen Output Delivered   | 457 lm (@ 10°, PW 3000 K) <b>TBC</b>  |   |  |
|   | Projected Lumen Maintenance  | L90B10 >90.000 hrs, Ta = 25°C / 77°F  |   |  |
| <b>CONTROL</b>                            | Interface protocol   | Via E-box Remote or E-box Remote Basic   ON/OFF (PW & single colour only)   |   |  |
|   | E-Box Remote control protocol  | USITT DMX512/RDM, ArtNet, MA Net, MA Net2, sACN, Kling-Net  |   |  |
|   | Setting / addressing   | E-box Remote, RDM communicator  |   |  |
|   | Connectivity & Power Supply  | E-Box Remote   Remote Basic   |   |  |
| <b>PHYSICAL</b>                           | Width x Height x Depth   | 94 x 112 x 224 mm (3.7 x 4.4 x 8.8 in.)   |   |  |
|   | Weight   | <b>0.6 kg   1.3 lbs</b>   |   |  |
|   | Housing  | High Pressure Die-Cast Aluminium Body   Tempered Glass  |   |  |
|   | Finish Options   | Standard Colour   | Graphite Black RAL 9011   Grey Aluminium RAL 9007<br>Pure White RAL 9010   Sandstone RAL 1014 |  |
|   |  | Standard Colour<br>Harsh Environment  | Graphite Black RAL 9011   Grey Aluminium RAL 9007<br>Pure White RAL 9010   Sandstone RAL 1014 |  |
|   |  | Cost Option   | Custom RAL  |  |
|   | Cabels / Connectivity  | <b>IN (for DMX, DALI):</b><br>- 1 m cable with bare end<br>- Other cable length - custom<br>- Junction box - optional | <b>IN (for E-Box Version):</b><br>- Cable (5x20 AWG) 0.5 m, with Connector MM                 |  |
|   | Mounting Method  | Yoke or Yoke for Pole Adaptor   |   |  |
|   | Adjustability  | +180° / -180°   |   |  |
|   | Protection Factor  | IP67 (IP66 Junction Box) / Suitable For Wet Locations   |   |  |
| IK Rating                                 | IK10   |   |   |  |
| Cooling System                            | Convection   |   |   |  |
| Operating Ambient Temperature             | -20°C / +50°C (-4°F / +122°F)  |   |   |  |
| <b>CERTIFICATION</b>                      | Listings   | ETL / cETL, CE, RoHS, UKCA  |   |  |
| <b>ACCESSORIES</b>                        | <b>Not Included Items</b>  | Re-enterable Electrical Insulating Resin  |   |  |
|   |  | Land Spike for Calumma XS   |   |  |
|   |  | Twin Wall Cover Calumma XS  |   |  |
|   |  | Pole Adaptor (ø 102 mm) (Yoke for Pole Adaptor Required)  |   |  |
|   |  | <b>Lenses for Calumma Arts XS</b>   | PC Lens   Fractal Lens   ARC Lens   Line Lens   |  |
| <b>Textured Glass for Calumma Arts XS</b> | Aerolite Glass   DewDrop Glass   Flo Glass   Ripple Glass   Cube Glass   CF Glass   CRF Glass   GF Glass   Cathedral Moorish |   |   |  |

|   |   |
|---|---|
|   | Junction Box Remote (1x Output)   |
|   | Junction Box Remote (4x Output)   |
| <b>IN</b><br>(1 m Cable with bare-end version)                | Cable UL20969 5x20 AWG (black or white) - Calumma XS input cable              |
|   | Cable SJTW 5x14 AWG (black or white) - main connection between Junction Boxes |
| <b>ACCESSORIES</b>  | Leader Cable FF 0.1 m CE AD-05  |
|   | Jumper Cable MM/FFCE AD-05 0.5 m   1 m   3 m   5 m                            |
|   | T-connector FMF CE AB-AD-05   |
|   | Waterproof Cap for M connector AD-05  |
|   | Waterproof Cap for F connector AD-05  |
| <b>IN</b><br>(0.5 m Cable 5x20 AWG with Connector MM version) | Cable SJTW 5x14 AWG (black or white) - main connection between Junction Boxes |
|   | Connection Box Remote 1x Out (14 AWG–20 AWG)                                  |
|   | Connection Box Remote 2x Out (14 AWG–14 AWG & 20 AWG)                         |
|   | Field Installable Connector FF DC-05 (for 5x14 AWG)                           |
|   | Field Installable Connector FM DC-05 (for 5x14 AWG)                           |

## CONTROL AND CONNECTION OPTIONS

### IN ( 1 m Cable with bare-end )

- 1) SJTW 5x14 AWG (13053693), Standard 1 m with bare-end, black or on request Cable SJTW 5x14 AWG (13053697), with bare-end, white
- 2) Junction Box Remote (4x Output)
- 3) Cable UL 20969 5x20 AWG (13053481), black or on request Cable UL 20969 5x20 AWG (13053696), white
- 4) Junction Box Remote (1x Output)




**CONTROL AND CONNECTION OPTIONS**

**IN (0.5 m Cable 5x20 AWG with Connector MM)**


- 1) SJTW 5x14 AWG (13053693), Standard 1 m with bare-end, black or on request Cable SJTW 5x14 AWG (13053697), white
- 2) Field Installable Connector FF DC-05 (13053971)
- 3) Connection Box Remote 1x Out (14 AWG–14 AWG & 20 AWG) Cable (5x20 AWG) 0.1 m, with Connector FF
- 4) T-connector FMF (13053935)
- 5) Cable 5x20 AWG (13053481) 0.5 m, with Connector MM

**Note: The last unmated connector must be fitted with an Waterproof Cap to protect the IP rating.**




- 1) SJTW 5x14 AWG (13053693), Standard 1 m with bare-end, black or on request Cable SJTW 5x14 AWG (13053697), white
- 2) Field Installable Connector FF DC-05 (13053971)
- 3) Connection Box Remote 2x Out (14 AWG–14 AWG & 20 AWG) Cable (5x20 AWG) 0.1 m, with Connector FF
- 4) Cable (5x20 AWG) 0.5 m, with Connector MM
- 5) Field Installable Connector FM DC-05 (13053973)

**Note: The last unmated connector must be fitted with an Waterproof Cap to protect the IP rating.**



**ON/OFF**

- 1) Cable UL 20969 5x20 AWG (13053481), black or on request Cable UL 20969 5x20 AWG (13053696), white
- 2) Junction Box Remote (4x Output)
- 3) Junction Box Remote (1x Output)




**CONNECTIVITY**

Following table shows maximum connected Calummas Arts XS SC in a row with respect of cable length.

| Cable length                    | Per E-Box Remote | Per 1 LED output |
|---------------------------------|------------------|------------------|
| 50 m (max per 1 output)         | 40 pcs           | 20 pcs           |
| 100 m (total length, 2x output) |                  | 20 pcs           |


**DIMENSIONS**



ACCESSORIES

Land Spike for Calumma XS

for Calumma XS



Pole Adaptor (ø 102 mm, Yoke for pole Adaptor Required / PA)

Example of ordering code: Calumma XS SC RGBCW 15° PA

