

# EMINERE® REMOTE MC 1 / 2 / 3 / 4

The newest member of the Eminere product range, Eminere Remote MC extends our series of linear architectural fixtures into further application possibilities using only low voltage for higher safety restrictions. Available in four sizes, ranging from 1 to 4 feet, Eminere Remote MC follows the identical optical and performance features of our other established and proven Eminere fixtures. Design-wise, Eminere Remote MC brings all of today's technology into an elegant and slim body, but is still very robust with an IP67 rating to withstand the harshest environments.



## KEY FEATURES

### Optic & Control

Output up to 938 lm (RGBW) per one foot of Eminere. With a wide range of optics for limitless fixture applications, Eminere Remote MC can also be operated in pixel (4 MC LEDs) or fixture modes, and its low-input voltages allow the luminaire to be used in applications with higher safety restrictions.

### Compact design

At only 52 mm of total height, Eminere Remote MC is the thinnest lighting solution in our Eminere series and has been designed as a compact and slim LED luminaire suitable for any low-profile application.

### Durability

Thanks to its tempered glass and high-pressure, extruded aluminum housing, Eminere Remote MC is IK06 and IP67 certified. For more extreme and marine applications, a harsh environment finish option is also available.

## COLOURS

\* UPON REQUEST



RGBW  
(6500 K)



RGBA



RGLB



PW  
(3000 K)



TW  
(3000-6500 K) \*

## CONTROL & PROTOCOLS



OPTIONAL

## FINISH OPTIONS

\* CLOSEST RAL TONE  
\* HE = Harsh Environment



Graphite Black  
RAL 9011\*



Grey Aluminium  
RAL 9007



Sandstone  
RAL 1014\*



Pure White  
RAL 9010



HE  
Graphite Black  
RAL 9011\*



HE  
Grey Aluminium  
RAL 9007



HE  
Sandstone  
RAL 1014\*



HE  
Pure White  
RAL 9010



Custom  
Paint Colour

## OPTIC OPTIONS

### SYMMETRICAL



12°



15°



25°



30°



45°



65°



100°

### BI-SYMMETRICAL



10°x30°



10°x60°



15°x45°



15°x90°



35°x60°



30°x90°

## STANDARD & SPECIFICATION



IP67



IK06



CE



ETL



ROHS



UK  
CA



5  
YEAR

Warranty  
with  
Registration



Vibration  
Standard  
for Bridge


SPECIFICATION

<b>ELECTRICAL</b>	Input Voltage	48 V			
	Typical Power Consumption	<b>Eminere Remote MC 1:</b> 20 W		<b>Eminere Remote MC 2:</b> 40 W	
		<b>Eminere Remote MC 3:</b> 60 W		<b>Eminere Remote MC 4:</b> 80 W	
<b>OPTICAL</b>	Light Source	4, 8, 12, 16 x High Power Multi Chip LEDs			
	Colour Variants	RGBW (W - 6500 K)   RGBA   RGBL   Pure White (W - 3000 K)			
		<b>On Request:</b> Tuneable White (3000–6500 K)			
	Beam Angle	Symmetrical:	12°   15°   25°   30°   45°   65°   100°		
		Bi-symmetrical:	10°x30°   10°x60°   15°x45°   15°x90°   35°x60°   30°x90°		
Lumen Output Delivered	<b>Eminere Remote MC 1:</b> 938 lm, (12°, @RGBCW)		<b>Eminere Remote MC 3:</b> 2814 lm, (12°, @RGBCW)		
	<b>Eminere Remote MC 2:</b> 1876 lm, (12°, @RGBCW)		<b>Eminere Remote MC 4:</b> 3752 lm, (12°, @RGBCW)		
	Projected Lumen Maintenance	L90B10 >90.000 hrs, Ta = 25°C / 77°F			
<b>CONTROL</b>	Interface Protocol	Via E-Box Remote range			
	E-Box Remote Control Protocols	USITT DMX512, RDM, ArtNet, MA Net, MA Net2, sACN, Kling-Net			
	Operating Modes	Pixel (12 LEDs/300mm) or Fixture mode			
	Setting / Addressing	Via Two Row LCD Display with Control Buttons on E-Box Remote or RDM communicator			
	Power Supply	Via E-Box Remote range			
	Connectivity	E-box Remote	16 pcs of Eminere Remote 1 (50m cable - total length) via 1 Output,		
		E-box Remote Basic	20 pcs in total for both Outputs (25m cable - total length)		
<b>PHYSICAL</b>	Width x Height x Length	<b>Eminere Remote MC 1</b>		113 x 52 x 329 mm (4.45 x 2.05 x 13 in.)	
		<b>Eminere Remote MC 2</b>		113 x 52 x 610 mm (4.45 x 2.05 x 24 in.)	
		<b>Eminere Remote MC 3</b>		113 x 52 x 914 mm (4.45 x 2.05 x 36 in.)	
		<b>Eminere Remote MC 4</b>		113 x 52 x 1219 mm (4.45 x 2.05 x 48 in.)	
	Weight	2.4 kg   5.3 lbs	3.3 kg   7.3 lbs	5.2 kg   11.5 lbs	6.7 kg   14.7 lbs
Housing	High Pressure Extruded Aluminium Body   End Caps - Die-Cast Aluminium   Tempered Glass				
Finish Options	Standard Colour	Graphite Black RAL 9011   Grey Aluminium RAL 9007 Pure White RAL 9010   Sandstone RAL 1014			
	Standard Colour Harsh Environment	Graphite Black RAL 9011   Grey Aluminium RAL 9007 Pure White RAL 9010   Sandstone RAL 1014			
	Cost Option	Custom RAL			
Cables / Connections	Integrated Junction Box				
Mounting Method	Surface Mount With Different Type of Brackets				
Adjustability	+30°				
Protection Factor	IP67 / Suitable For Wet Locations				
IK Rating	IK06				
Cooling System	Convection				
Operating Ambient Temperature	-20 °C / +40 °C (-4 °F / +104 °F)				
Operating Temperature	+67 °C @ Ambient +40 °C (+153 °F @ Ambient +104 °F)				
<b>CERTIFICATION</b>	Listings	ETL / cETL, CE, RoHS, UKCA			

**Not Included Items**

	Cabel for Eminere Remote - bare end (custom length)
	Field Installable Connector FF DC-05
	Field Installable Connector MM DC-05
<b>ACCESSORIES</b>	Optical Demo Set for Eminere Remote MC
Mounting Brackets	Mounting Brackets 100   200   300 mm   custom length
	Wall Mount Brackets for Eminere Remote
	Re-enterable Electrical Insulating Resin
Shields	Shield For Eminere Remote MC (with or without Side Covers) 1   2   3   4

**DIMENSIONS**



**PHOTOMETRIC OVERVIEW**


Based on RGBCW version, all leds @ full

Lumen Output (lm)

	EMINERE REMOTE MC 1	EMINERE REMOTE MC 2	EMINERE REMOTE MC 3	EMINERE REMOTE MC 4
12°	938	1876	2814	3752
15°	868	1736	2604	3472
25°	870	1739	2609	3478
35°	871	1741	2612	3482
45°	865	1729	2594	3458
65°	996	1728	2592	3456
100°	837	1673	2510	3346
10° x 30°	871	1741	2612	3482
10° x 60°	853	1705	2558	3410
15° x 45°	876	1752	2628	3504
15° x 90°	864	1727	2591	3454
30° x 90°	846	1691	2537	3382
35° x 60°	860	1719	2579	3438

**BI-SYMMETRICAL BEAM ANGLES**


Bi-symmetrical: 10°x30°, 10°x60°, 15°x45°, 15°x90°, 35°x60°, 30°x90°



**CONNECTION**

The table states max. number of Eminere Remote modules connected to the E-box Remote or Remote Basic.

Cable length (m)	Max. number of Emineres Remote connected to the E-Box Remote or Remote Basic			
	EMINERE REMOTE 1	EMINERE REMOTE 2	EMINERE REMOTE 3	EMINERE REMOTE 4
25	20	10	6	5
50	16	8	5	4
75	13	6	4	3
100	10	5	3	2



1) SJTW 5x14 AWG (13053693), black or on request Cable SJTW 5x14 AWG (13053697), white


\* Cable length is a total cable length between E-box Remote (or Remote Basic) and last connected Eminere Remote. Example: Total cable length=L1+L2+L3+L4

**CONNECTION**

Standard

- 1) SJTW 5x14 AWG (13053693), Standard 1 m with bare-end, black  
or on request Cable SJTW 5x14 AWG (13053697), with bare-end, white
- 2) Field Installable Connector FF DC-05 (13053971)
- 3) Field Installable Connector MM DC-05 (13053972)


**Note: The last unmated connector must be fitted with an Waterproof Cap to protect the IP rating.**



Right Input - (RI)

- 1) SJTW 5x14 AWG (13053693), Standard 1 m with bare-end, black  
or on request Cable SJTW 5x14 AWG (13053697), with bare-end, white
- 2) Field Installable Connector FF DC-05 (13053971)
- 3) Field Installable Connector MM DC-05 (13053972)

**Note: The last unmated connector must be fitted with an Waterproof Cap to protect the IP rating.**




**E-BOX REMOTE SPECIFICATION**

<b>ELECTRICAL</b>	Input Voltage	120 – 277 V AC 50/60 Hz
	Typical Power Consumption	520 W
<b>CONTROL</b>	Wireless DMX (Option)	Lumen Radio CRMX Technology
	Interface Protocol	USITT DMX512+RDM, ArtNet, MA Net, MA Net2, sACN, Kling-Net
	Operating Modes	Fixture Mode, Pixel Mode, Output Mode
	Display	Via Two Row LCD Display with Control Buttons or RDM communicator
	Control System	E-box With Self Addressing Feature or Custom Setting Via LCD Display/RDM
	Power Supply	Integrated in E-box Remote
	Connectivity	16 pcs of Eminere Remote 1 (50m cable - total length) via 1 Output, 20 pcs in total for both Outputs (25m cable - total length)
	<b>PHYSICAL</b>	Length x Width x Height   Weight
	Number of LED Output zones	2
	Max. Load Per Output	16 pcs of Eminere Remote 1 (50m cable) via 1 Output
	Cable Length per E-Box	Max. 25 m (@ 20 pcs)   Max. 50 m (@ 16 pcs)   Max. 75 m (@ 13 pcs)   Max. 100 m (@ 10 pcs)
	Housing	Die-Cast Aluminium Case
	Finish Options	Standard Colour - Graphite Black (RAL 9011)   Silver (RAL 9006) Cost Option - Custom RAL   Harsh Environment (RAL 9016, RAL 9011)
	Cables / Connections	Cable Grommet (stainless steel)
	Mounting Method	Surface Mount, 4 Mounting Holes
	Protection Factor	IP65 / Suitable For Wet Locations
	IK Rating	IK10
	Cooling System	Convection
	Operating Ambient Temperature	-20 °C / +40 °C (-4 °F / +104 °F)
<b>CERTIFICATION</b>	Listings	ETL / cETL, CE, RoHS, UKCA


**E-BOX REMOTE BASIC SPECIFICATION**

<b>ELECTRICAL</b>	Input Voltage	120 - 277 V AC 50/60 Hz
	Typical Power Consumption	520 W
<b>CONTROL</b>	Power supply	Integrated
	Connectivity	16 pcs of Eminere Remote 1 (50m cable - total length) via 1 Output, 20 pcs in total for both Outputs (25m cable - total length)
<b>PHYSICAL</b>	Length x Width x Height   Weight	360 x 210 x 91 mm (14.17 x 8.27 x 3.58 in.)   5 kg / 11.02 lbs
	Number of LED Output zones	2
	Max. Load Per Output	16 pcs of Eminere Remote 1 (50 m cable) via 1 Output
	Cable Length per E-Box	Max. 25 m (@ 20 pcs)   Max. 50 m (@ 16 pcs)   Max. 75 m (@ 13 pcs)   Max. 100 m (@ 10 pcs)
	Housing	Die-Cast Aluminium Case
	Finish Options	Standard Colour - Graphite Black (RAL 9011)   Silver (RAL 9006) Cost Option - Custom RAL,   Harsh Environment (RAL 9016, RAL 9011)
	Cables / Connections	Cable Grommet (stainless steel)
	Mounting Method	Surface Mount, 4 Mounting Holes
	Protection Factor	IP65 / Suitable For Wet Locations
	IK Rating	IK10
	Cooling System	Convection
	Operating Ambient Temperature	-20 °C / +40 °C (-4 °F / +104 °F)
	<b>CERTIFICATION</b>	Listings

E-BOX REMOTE DIMENSIONS





E-BOX REMOTE BASIC DIMENSIONS





PHOTOMETRIC DATA



Eminere Remote MC 4 RGBCW 12dg





Eminere Remote MC 4 RGBCW 15dg





Eminere Remote MC 4 RGBCW 25dg





Eminere Remote MC 4 RGBCW 35dg



Eminere Remote MC 4 RGBCW 65dg




Eminere Remote MC 4 RGBCW 100dg




PHOTOMETRIC DATA


Eminere Remote MC 4 RGBCW  
10dg x 30dg








Eminere Remote MC 4 RGBCW  
10dg x 60dg




Eminere Remote MC 4 RGBCW  
15dg x 45dg



Eminere Remote MC 4 RGBCW  
15dg x 90dg



Eminere Remote MC 4 RGBCW  
30dg x 90dg



Eminere Remote MC 4 RGBCW  
35dg x 60dg

